

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Article  
 Product name : Pro-Line® WP PAINT MARKER  
 Synonyms : Pro-Line® WP PAINT MARKER - Black, Blue, Green, Orange, Silver, White, Yellow, Red

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Use of the substance/mixture : Paint

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

LA-CO Industries Europe S.A.S.  
 Parc Industriel de la Plaine de  
 l'Ain - Allée des Combes.  
 01150.BLYES.France.  
 Phone: +33 (0)4 74 46 23 23  
 Fax: +33 (0)4 74 46 23 29  
 E-mail: info@eu.laco.com  
 Web: http://www.markal.com

**1.4. Emergency telephone number**

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request  
 EUH208 - Contains [N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylamino(2-)-N29,N30,N31,N32]copper(28654-73-1), 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)(2786-76-7). May produce an allergic reaction

**2.3. Other hazards**

PBT: not yet assessed

vPvB: not yet assessed

**SECTION 3: Composition/information on ingredients****3.1. Substance**

Not applicable

**3.2. Mixture**

Comments : Only component with health hazards above the applicable thresholds and/or Exposure Limit values are shown

Exact concentrations are withheld as trade secret

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cyclohexanone	(CAS No) 108-94-1 (EC no) 203-631-1 (EC index no) 606-010-00-7	10 – 30	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:dust,mist), H332
tert-butyl acetate	(CAS No) 540-88-5 (EC no) 208-760-7 (EC index no) 607-026-00-7	20 – 60	Flam. Liq. 2, H225

# Pro-Line® WP PAINT MARKER

## Safety Data Sheet

according to Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
titanium dioxide	(CAS No) 13463-67-7 (EC no) 236-675-5	0 – 40	Not classified
aluminium powder (stabilised)	(CAS No) 7429-90-5 (EC no) 231-072-3 (EC index no) 013-001-00-1	0 – 10	Flam. Sol. 1, H228 Water-react. 2, H261
Carbon black	(CAS No) 1333-86-4 (EC no) 215-609-9	0 – 5	Carc. 2, H351
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)	(CAS No) 2786-76-7 (EC no) 220-509-3	0 – 5	Skin Sens. 1, H317
Aluminum hydroxide	(CAS No) 21645-51-2 (EC no) 244-492-7	0 – 2	Not classified
2-methoxy-1-methylethyl acetate	(CAS No) 108-65-6 (EC no) 203-603-9 (EC index no) 607-195-00-7	0 – 2	Flam. Liq. 3, H226
Ethyl acetate	(CAS No) 141-78-6 (EC no) 205-500-4 (EC index no) 607-022-00-5	0.1 – 2	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Aluminum oxide	(CAS No) 1344-28-1 (EC no) 215-691-6	0 – 1	Not classified
Butyl acetate	(CAS No) 123-86-4 (EC no) 204-658-1 (EC index no) 607-025-00-1	0 – 0.5	Flam. Liq. 3, H226 STOT SE 3, H336
[N,N,N',N'',N''',N'''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper	(CAS No) 28654-73-1 (EC no) 249-125-4	0 – 0.5	Skin Sens. 1B, H317
barium sulfate	(CAS No) 7727-43-7 (EC no) 231-784-4	0 – 0.5	Not classified
Toluene	(CAS No) 108-88-3 (EC no) 203-625-9 (EC index no) 601-021-00-3	< 0.1	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336
2-methoxypropyl acetate	(CAS No) 70657-70-4 (EC no) 274-724-2 (EC index no) 607-251-00-0	< 0.1	Flam. Liq. 3, H226 Repr. 1B, H360D STOT SE 3, H335

Full text of R- and H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
- First-aid measures after ingestion : Do NOT induce vomiting. Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : None known.

#### 4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Inert gas. Foam. Water spray. Water fog.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour. Burning produces irritating, toxic and noxious fumes.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

#### 5.3. Advice for firefighters

- Firefighting instructions : Eliminate all ignition sources if safe to do so. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus. EN469.

# Pro-Line® WP PAINT MARKER

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Emergency procedures : Ventilate area. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

#### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools. Avoid all eye and skin contact and do not breathe vapour and mist.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment.

Storage conditions : Keep in fireproof place. Keep container closed when not in use.

Incompatible products : Oxidizer.

Incompatible materials : Heat sources.

Heat and ignition sources : Keep away from heat, sparks and flame.

Prohibitions on mixed storage : Incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

#### 7.3. Specific end use(s)

Marking.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Ethyl acetate (141-78-6)		
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	730 mg/m <sup>3</sup>
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1460 mg/m <sup>3</sup>
Toluene (108-88-3)		
EU	IOELV TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
Carbon black (1333-86-4)		
United Kingdom	Local name	Carbon black
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Aluminum oxide (1344-28-1)		
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable aerosol) 4 mg/m <sup>3</sup> (respirable aerosol)
titanium dioxide (13463-67-7)		
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> inhalable aerosol 4 mg/m <sup>3</sup> respirable aerosol

# Pro-Line® WP PAINT MARKER

## Safety Data Sheet

according to Regulation (EU) 2015/830

barium sulfate (7727-43-7)		
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> inhalable aerosol 4 mg/m <sup>3</sup> respirable aerosol
aluminium powder (stabilised) (7429-90-5)		
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable dust) 4 mg/m <sup>3</sup> (respirable dust)

### 8.2. Exposure controls

Appropriate engineering controls	: Avoid splashing. Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: None under normal use.
Eye protection	: None under normal use.
Respiratory protection	: None under normal use.
Other information	: Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Variable.
Odour	: Solvent.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 97.8 °C
Flash point	: 16.6 - 22.2 °C
Auto-ignition temperature	: 426 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.96 - 1.34
Solubility	: insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: 50 - 80 %
-------------	-------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Open flame. Direct sunlight.

### 10.5. Incompatible materials

Oxidizer.

# Pro-Line® WP PAINT MARKER

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 10.6. Hazardous decomposition products

May release flammable gases. Burning produces irritating, toxic and noxious fumes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity** : Inhalation:dust,mist: Not classified.

<b>Cyclohexanone (108-94-1)</b>	
ATE CLP (dust,mist)	1.500 mg/l/4h
<b>tert-butyl acetate (540-88-5)</b>	
LD50 oral rat	4100 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	4211 ppm 6 h
ATE CLP (oral)	4100.000 mg/kg bodyweight
<b>Ethyl acetate (141-78-6)</b>	
LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (mg/l)	> 18 mg/l/4h
ATE CLP (oral)	5620.000 mg/kg bodyweight
<b>Toluene (108-88-3)</b>	
LD50 oral rat	5580 mg/kg EU Method B.1 (Acute Toxicity (Oral))
LC50 inhalation rat (mg/l)	> 20 mg/l/4h OECD Guideline 403 (Acute Inhalation Toxicity)
ATE CLP (oral)	5580.000 mg/kg bodyweight
<b>Carbon black (1333-86-4)</b>	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m <sup>3</sup> 4 h
<b>Aluminum oxide (1344-28-1)</b>	
LD50 oral rat	> 15900 mg/kg
LC50 inhalation rat (mg/l)	7.6 mg/l/4h
ATE CLP (vapours)	7.600 mg/l/4h
ATE CLP (dust,mist)	7.600 mg/l/4h
<b>titanium dioxide (13463-67-7)</b>	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 6.82 mg/l/4h
<b>Butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 inhalation rat (mg/l)	> 21 mg/l/4h
ATE CLP (oral)	10760.000 mg/kg bodyweight
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LD50 oral rat	8532 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (ppm)	4345 ppm 6 h
ATE CLP (oral)	8532.000 mg/kg bodyweight
<b>2-methoxypropyl acetate (70657-70-4)</b>	
LC50 inhalation rat (ppm)	2700 ppm 6 h
<b>barium sulfate (7727-43-7)</b>	
LD50 oral rat	307 g/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	307000.000 mg/kg bodyweight
<b>[N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylamino(2-)-N29,N30,N31,N32]copper (28654-73-1)</b>	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rat	> 2500 mg/kg
<b>aluminium powder (stabilised) (7429-90-5)</b>	
LD50 oral rat	> 15900 mg/kg
LC50 inhalation rat (mg/l)	> 2.3 mg/l/4h No mortality observed in this study.

# Pro-Line® WP PAINT MARKER

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

LD50 oral rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	> 1580 mg/m <sup>3</sup> 4 h

<b>Skin corrosion/irritation</b>	: Not classified
<b>Serious eye damage/irritation</b>	: Not classified
<b>Respiratory or skin sensitisation</b>	: Not classified.
<b>Germ cell mutagenicity</b>	: Not classified
<b>Carcinogenicity</b>	: Not classified.

### titanium dioxide (13463-67-7)

NOAEL (chronic, oral, animal/male, 2 years)	5 mg/kg bodyweight rat
---	------------------------

### barium sulfate (7727-43-7)

NOAEL (chronic, oral, animal/male, 2 years)	60 mg/kg bodyweight
NOAEL (chronic, oral, animal/female, 2 years)	75 mg/kg bodyweight

<b>Reproductive toxicity</b>	: Not classified
<b>Specific target organ toxicity (single exposure)</b>	: Not classified
<b>Specific target organ toxicity (repeated exposure)</b>	: Not classified

### Toluene (108-88-3)

LOAEL (inhalation, rat, gas, 90 days)	1250 ppmv/6h/day
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight/day EU Method B.26. Increased relative weights of liver and kidney are interpreted as toxicologically insignificant differences in the absence of histological findings.
NOAEL (inhalation, rat, gas, 90 days)	300 ppmv/6h/day OECD Guideline 453

<b>Aspiration hazard</b>	: Not classified
--------------------------	------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

#### tert-butyl acetate (540-88-5)

LC50 fish 1	240 mg/l 96 h
EC50 Daphnia 1	410 mg/l 24 h

#### Ethyl acetate (141-78-6)

LC50 fish 1	220 mg/l
EC50 Daphnia 1	1200 mg/l
NOEC chronic fish	< 9.35 mg/l

#### Toluene (108-88-3)

LC50 fish 1	5.5 mg/l
EC50 Daphnia 2	3.78 mg/l
ErC50 (algae)	134 mg/l
LOEC (chronic)	2.77 mg/l
NOEC chronic fish	1.39 mg/l
NOEC chronic crustacea	0.74 mg/l

#### Aluminum oxide (1344-28-1)

EC50 Daphnia 1	> 1470 mg/l
NOEC (acute)	> 50 mg/l

#### 2-methoxy-1-methylethyl acetate (108-65-6)

LC50 fish 1	100 - 180 mg/l
EC50 Daphnia 1	> 500 mg/l 48 h
ErC50 (algae)	> 1000 mg/l

#### barium sulfate (7727-43-7)

LC50 fish 1	> 3.5 mg/l 96 h
EC50 Daphnia 1	14500 µg/l 48 h

#### [N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)

LC50 fish 1	> 146 mg/l 96 h
EC50 Daphnia 1	> 100 mg/l 48 h

# Pro-Line® WP PAINT MARKER

## Safety Data Sheet

according to Regulation (EU) 2015/830

aluminium powder (stabilised) (7429-90-5)	
LC50 fish 1	> 218.64 mg/l ASTM 2000; test material: aluminium chloride hexahydrate; Pimephales promelas
EC50 Daphnia 1	1.4 mg/l OECD Guideline 202; test material: Aluminium hydroxide
LOEC (acute)	72.89 mg/l
NOEC (acute)	37.2 mg/l

  

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LC50 fish 1	> 500 mg/l 96 h
EC50 Daphnia 1	> 110 mg/l 48 h

### 12.2. Persistence and degradability

tert-butyl acetate (540-88-5)	
Persistence and degradability	Readily biodegradable.
Biodegradation	50 % 28 d

  

Ethyl acetate (141-78-6)	
Persistence and degradability	Readily biodegradable.

  

Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.

  

Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.

  

2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Readily biodegradable.
Biodegradation	89 % 10 d

  

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d

### 12.3. Bioaccumulative potential

tert-butyl acetate (540-88-5)	
BCF fish 1	5.61
Log Pow	1.64

  

Ethyl acetate (141-78-6)	
Bioaccumulative potential	Not expected to bioaccumulate.

  

Toluene (108-88-3)	
Bioconcentration factor (BCF REACH)	90
Log Kow	2.73

  

2-methoxy-1-methylethyl acetate (108-65-6)	
Log Pow	0.43

  

barium sulfate (7727-43-7)	
BCF fish 1	68.4 L/kg

  

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
BCF fish 1	53 l/kg
Log Pow	1.28

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

Pro-Line® WP PAINT MARKER	
PBT: not yet assessed	
vPvB: not yet assessed	

  

Component	
Ethyl acetate (141-78-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

# Pro-Line® WP PAINT MARKER

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
European List of Waste (LoW) code	: For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used
H code	: H3-A - 'Highly flammable' : — liquid substances and preparations having a flash point below 21 °C (including extremely flammable liquids), or — substances and preparations which may become hot and finally catch fire in contact with air at ambient temperature without any application of energy, or — solid substances and preparations which may readily catch fire after brief contact with a source of ignition and which continue to burn or to be consumed after removal of the source of ignition, or — gaseous substances and preparations which are flammable in air at normal pressure, or — substances and preparations which, in contact with water or damp air, evolve highly flammable gases in dangerous quantities

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR)	: 1263
UN-No. (IATA)	: 1263
UN-No. (IMDG)	: 1263
UN-No. (ADN)	: 1263

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Paint
Proper Shipping Name (IATA)	: Paint
Proper Shipping Name (IMDG)	: PAINT
Proper Shipping Name (ADN)	: PAINT
Transport document description (ADR)	: UN 1263 PAINT, 3, II, (D/E)

#### 14.3. Transport hazard class(es)

Class (ADR)	: 3
Classification code (ADR)	: F1
Class (IATA)	: 3
Class (IMDG)	: 3
Class (ADN)	: 3
Classification code (ADN)	: F1

#### 14.4. Packing group

Packing group (ADR)	: II
Packing group (IATA)	: II
Packing group (IMDG)	: II
Packing group (ADN)	: II

#### 14.5. Environmental hazards

Other information	: No supplementary information available.
-------------------	---

#### 14.6. Special precautions for user

##### 14.6.1. Overland transport

Hazard identification number (Kemler No.)	: 33
Classification code (ADR)	: F1
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

##### 14.6.2. Transport by sea

EmS-No. (Fire)	: F-E
----------------	-------

# Pro-Line® WP PAINT MARKER

## Safety Data Sheet

according to Regulation (EU) 2015/830

EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : B

### 14.6.3. Inland waterway transport

Carriage prohibited (ADN) : No

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substance on the REACH candidate list

VOC content : 50 - 80 %

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

according to Regulation (EU) 2015/830

Indication of changes:

Original Document.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weighted Average
	TSCA: Toxic Substances Control Act

Data sources : ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.  
European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.  
National Fire Protection Association; Fire Protection Guide to Hazardous Materials; 10th edition.  
OSHA 29CFR 1910.1200 Hazard Communication Standard.  
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.  
TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
Repr. 1B	Reproductive toxicity, Category 1B

# Pro-Line® WP PAINT MARKER

## Safety Data Sheet

according to Regulation (EU) 2015/830

Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
Skin Sens. 1B	Sensitisation — Skin, category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H228	Flammable solid
H261	In contact with water releases flammable gases
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H360D	May damage the unborn child
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
EUH208	Contains . May produce an allergic reaction
EUH210	Safety data sheet available on request
R10	Flammable
R11	Highly flammable
R15	Contact with water liberates extremely flammable gases
R20	Harmful by inhalation
R36	Irritating to eyes
R37	Irritating to respiratory system
R38	Irritating to skin
R40	Limited evidence of a carcinogenic effect
R43	May cause sensitisation by skin contact
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R61	May cause harm to the unborn child
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
Xi	Irritant
Xn	Harmful

LA-CO EU CLP SDS United Kingdom

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43016  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*