

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 30/08/2005

Revision date: 14/04/2015

Supersedes: 17/11/2008

Version: 3.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Article  
 Trade name : PRO-WASH™ D Detergent Removable Paint Markers  
 Synonyms : PRO-WASH™ D Detergent Removable Paint Markers White, Yellow, Black, Blue, Green, Red

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
 Use of the substance/mixture : Marking.

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

LA-CO Industries Europe S.A.S.  
 Parc Industriel de la Plaine de  
 l'Ain - Allée des Combes.  
 01150.BLYES.France.  
 Phone: +33 (0)4 74 46 23 23  
 Fax: +33 (0)4 74 46 23 29  
 E-mail: info@eu.laco.com  
 Web: http://www.markal.com



#### 1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
AUSTRIA	Vergiftungsinformationszentrale (Poisons Information Centre)	Allgemeines Krankenhaus Waehringer Geurtel 18-20 1090 Wien	+43 1 406 43 43
BELARUS	The Belarus Republican Poisons Centre	Kizhevatova str. 58 220115 Minsk	+375 (0)17 201 9158
BELGIUM	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245
BULGARIA	Национален токсикологичен информационен център National Clinical Toxicology Centre, Emergency Medical Institute "Pirogov"	21 Tottleben Boulevard 1606 SOFIA	+359 2 9154 409
CROATIA	Poisons Control Centre Institute of Medical Research & Occupational Health	Ksaverska Cesta 2 P.O. Box 291 HR-10000 Zagreb	+385 1 234 8342
CZECH REPUBLIC	Toxikologické informační středisko Clinic For Occupational Medicine, 1st Medical Faculty, Charles University	Na Bojišti 1 120 00 Praha 2	+42 2 2491 9293 +42 2 2491 5402
DENMARK	Gifflinjen Bispebjerg Hospital	Bispebjerg Bakke 23, 60, 1 DK-2400 København NV	+45 82 12 12 12 +45 35 31 55 55
ESTONIA	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	+372 626 93 90
FINLAND	Myrkytystietokeskus	P.O.B 340 (Haartmaninkatu 4) HUS SF - 00029 Helsinki	+358 9 471 977
FRANCE	ORFILA		+33 1 45 42 59 59
GERMANY	Berliner Betrieb für Zentrale Gesundheitliche Aufgaben	Oranienburger Strasse 285 13437 Berlin	+49 30 19240
GERMANY	Informations und Beratungszentrum für Vergiftungsfälle	Kirrberger Straße, Gebäude 9 D-66421 Homburg/Saar	+49 6841 19240
GERMANY	Beratungstelle bei Vergiftungen, Klinische Toxikologie und Beratungsstelle bei Vergiftungen	Langenbeckstrasse 1 55131 Mainz	+49 6131 19240
GREECE	Poisons Information Centre	11527 Athens	+30 10 779 3777
HUNGARY	Országos Kémiai Biztonsági Intézet (National Institute of Chemical Safety) Egészségügyi Toxikológiai Tájékoztató Szolgálat (Health Toxicological Information Service)	1437 Budapest PO Box 839 1097 Budapest, Nagyvárad tér 2	+36 80 20 11 99
ICELAND	Eitrunarmiðstöðin	Eitrunarmiðstöðin 108 Reykjavik	+354 543 22 22

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

IRELAND	National Poisons Information Centre	Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166
LATVIA	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs	2 Hipocrate Street LV 1038 Riga	+371 67 04 24 73
LITHUANIA	Apsinuodijimų kontrolės ir informacijos biuras	Siltnamiu 29 2043 Vilnius	+370 5 236 20 52/+370 687 53 378
MALTA	Medicines & Poisons Info Office	Mater Dei Hospital, Msida MSD 2090 Malta	25450000
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88
PORTUGAL	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica (INEM)	Rua Almirante Barroso, 36 1000-013 Lisboa	808 250 143 (for use only in Portugal), +351 21 330 3284
ROMANIA	Biroul pentru Regulamentul Sanitar International si Informare Toxicologica	Str. Dr. Leonte Anastasievici Nr.1-3, Sector 5 50463 Bucuresti	+40 21 318 36 06
SLOVAKIA	Národné toxikologické informačné centrum University Hospital Bratislava	Limbová 5 833 05 Bratislava	+421 2 54 77 4 166
SPAIN	Servicio de Información Toxicológica Instituto Nacional de Toxicología, Departamento de Madrid	Calle Luis Cabrera 9 E-28002 Madrid	+34 91 562 04 20
SWEDEN	Giftinformationscentralen Swedish Poisons Information Centre, Karolinska Hospital	Box 60 500 SE-171 76 Stockholm	+46 8 33 12 31 (International) 112 (National)
SWITZERLAND	Centre Suisse d'Information Toxicologique	Freiestrasse 16 Postfach CH-8028 Zurich	+41 44 251 51 51 (International) 145 (National)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH phrases : EUH210 - Safety data sheet available on request

### 2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5	40 – 60	Flam. Liq. 2, H225
Titanium dioxide	(CAS No) 13463-67-7 (EC no) 236-675-5	0 – 25	Not classified
Isopropanol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0	1 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Docusate sodium USP	(CAS No) 577-11-7	1 – 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170	(CAS No) 2786-76-7 (EC no) 220-509-3	0 – 5	Skin Sens. 1, H317 (Naphthol <1%)
propyl acetate	(CAS No) 109-60-4 (EC no) 203-686-1 (EC index no) 607-024-00-6	1 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
C.I. Solvent Black 29	(CAS No) 117527-94-3 (EC no) 403-720-7 (EC index no) 611-044-00-0	0 – 2	Aquatic Chronic 2, H411

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Aluminum hydroxide	(CAS No) 21645-51-2 (EC no) 244-492-7	0 – 2	Not classified
2-methoxy-1-methylethyl acetate	(CAS No) 108-65-6 (EC no) 203-603-9 (EC index no) 607-195-00-7	0.1 – 1	Flam. Liq. 3, H226
Aluminum oxide	(CAS No) 1344-28-1 (EC no) 215-691-6	0 – 1	Not classified
Butyl acetate	(CAS No) 123-86-4 (EC no) 204-658-1 (EC index no) 607-025-00-1	0.01 – 1	Flam. Liq. 3, H226 STOT SE 3, H336
2-methoxypropyl acetate	(CAS No) 70657-70-4 (EC no) 274-724-2 (EC index no) 607-251-00-0	< 0.1	Flam. Liq. 3, H226 Repr. 1B, H360D STOT SE 3, H335

Full text of R- and H-phrases: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.
- First-aid measures after eye contact : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : May cause moderate irritation.
- Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.

#### 4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Foam. Water spray. Water fog.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Hazardous decomposition products in case of fire : Carbon oxides (CO, CO<sub>2</sub>).

#### 5.3. Advice for firefighters

- Firefighting instructions : Cool adjacent structures and containers with water spray to protect and prevent ignition. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus. EN469.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Stop the flow of material, if this is without risk.

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take up in non-combustible absorbent material and shove into container for disposal.

### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.  
Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools. Avoid all eye and skin contact and do not breathe vapour and mist.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use only non-sparking tools.  
Storage conditions : Keep in fireproof place. Keep container tightly closed.  
Incompatible products : Strong oxidizers.  
Incompatible materials : Heat sources.  
Heat and ignition sources : Keep away from heat, sparks and flame.  
Prohibitions on mixed storage : Keep away from incompatible materials.  
Storage area : Store in dry, cool, well-ventilated area.

### 7.3. Specific end use(s)

Marking.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

ethanol (64-17-5)		
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	3800 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	2000 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	960 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	500 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	1910 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	1000 ppm
Spain	Notes	s,
Isopropanol (67-63-0)		
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	400 ppm
Germany	TRGS 903 (BGW)	50 mg/l Aceton (Blut; Expositionsende bzw. Schichtende)
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	650 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 8H (ppm)	250 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup> VLB, s
Spain	VLA-ED (ppm)	200 ppm VLB, s 40 ppm F, I "(Acetona en orina; Final de la semana, laboral 1)"
Spain	VLA-EC (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup> VLB, s
Spain	VLA-EC (ppm)	400 ppm VLB, s
propyl acetate (109-60-4)		
Austria	Remark (AT)	(gemessen als Momentanwert)
Czech Republic	Remark (CZ)	I
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	1250 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	300 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	100 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	849 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	200 ppm

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

<b>propyl acetate (109-60-4)</b>		
Spain	VLA-EC (mg/m <sup>3</sup> )	1060 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	250 ppm
<b>Butyl acetate (123-86-4)</b>		
Austria	MAK (mg/m <sup>3</sup> )	480 mg/m <sup>3</sup>
Austria	MAK (ppm)	100 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	480 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	100 ppm
Austria	Remark (AT)	(gemessen als Momentanwert)
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	1420 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	300 ppm
Lithuania	IPRV (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	100 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	700 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	150 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	100 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	724 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	150 ppm
Spain	VLA-EC (mg/m <sup>3</sup> )	965 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	200 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	700 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	150 ppm
Norway	Gjennomsnittsverdier (AN) (mg/m <sup>3</sup> )	355 mg/m <sup>3</sup>
Norway	Gjennomsnittsverdier (AN) (ppm)	75 ppm
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>		
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	550 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	100 ppm
Finland	Huomautus (FI)	iho
France	Note (FR)	Peau
Germany	TRGS 900 Limitation of exposure peaks (mg/m <sup>3</sup> )	270 mg/m <sup>3</sup>
Germany	TRGS 900 Limitation of exposure peaks (ppm)	50 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	275 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	50 ppm
Slovakia	Upozornenie (SK)	(K)
Spain	VLA-ED (mg/m <sup>3</sup> )	275 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	50 ppm
Spain	VLA-EC (mg/m <sup>3</sup> )	550 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	100 ppm
Spain	Notes	VLI
Sweden	Anmärkning (SE)	H
<b>2-methoxypropyl acetate (70657-70-4)</b>		
Czech Republic	Remark (CZ)	D
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	40 ppm
Germany	TRGS 900 Limitation of exposure peaks (mg/m <sup>3</sup> )	224 mg/m <sup>3</sup>
Germany	TRGS 900 Limitation of exposure peaks (ppm)	40 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	110 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	20 ppm
Slovakia	Upozornenie (SK)	(K)
Spain	VLA-ED (mg/m <sup>3</sup> )	28 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	5 ppm
Spain	VLA-EC (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	40 ppm

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

<b>2-methoxypropyl acetate (70657-70-4)</b>		
Spain	Notes	TR1B,r
<b>Titanium dioxide (13463-67-7)</b>		
Belgium	Remark (BE)	(dioxyde de)
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	12 mg/m <sup>3</sup>
France	Note (FR)	inhalable aerosol
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> total inhalable dust 4 mg/m <sup>3</sup> respirable dust
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Spain	VLA-ED (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Spain	Notes	inhalable aerosol
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Sweden	Anmärkning (SE)	total dust, 1
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> inhalable aerosol 4 mg/m <sup>3</sup> respirable aerosol
Switzerland	Remark (CH)	(respirable aerosol)
<b>Aluminum oxide (1344-28-1)</b>		
Austria	MAK (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (gemessen als einatembarer Aerosolanteil) 5 mg/m <sup>3</sup> (alveolengängiger Anteil)
Austria	MAK Short time value (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (gemessen als einatembarer Aerosolanteil) max. 2x60 min./Schicht 10 mg/m <sup>3</sup> (alveolengängiger Anteil) max. 2x60 min./Schicht
Belgium	Limit value (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Belgium	Remark (BE)	(oxyde d') (en Al)
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (total) 2 mg/m <sup>3</sup> (respirabel)
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total) 4 mg/m <sup>3</sup> (respirabel)
France	VME (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
France	Note (FR)	(respirable aerosol)
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Germany	Remark (TRGS 900)	(gemessen als alveolengängiger Staubanteil)
Hungary	AK-érték	6 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	(respirable aerosol)
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total inhalable dust) 4 mg/m <sup>3</sup> (respirable dust)
Lithuania	IPRV (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Lithuania	Remark (LT)	(alveolinė frakcija. Piūrėk IX skyriaus 3 pastabà.)
Poland	NDS (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup> (dymy, pyl calkowity) 1.2 mg/m <sup>3</sup> (dymy, pyl respirabilny)
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (respirabilná frakcia) 4 mg/m <sup>3</sup> (inhalovateľná frakcia)
Spain	VLA-ED (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (inhalable aerosol) 2 mg/m <sup>3</sup> (respirable aerosol)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable aerosol) 4 mg/m <sup>3</sup> (respirable aerosol)
Norway	Gjennomsnittsverdier (AN) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Norway	Merknader (NO)	1)
Switzerland	VME (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Switzerland	Remark (CH)	(respirable aerosol)
<b>Aluminum hydroxide (21645-51-2)</b>		
Austria	MAK (ppm)	10 ppm (gemessen als einatembarer Aerosolanteil) 5 ppm (alveolengängiger Anteil)
Austria	MAK Short time value (ppm)	20 ppm (gemessen als einatembarer Aerosolanteil) max. 2x60 min./Schicht 10 ppm (alveolengängiger Anteil) max. 2x60 min./Schicht

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Aluminum hydroxide (21645-51-2)		
Poland	NDS (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup> dymy, pyl calkowity 1.2 mg/m <sup>3</sup> dymy, pyl respirabilny
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (respirabilná frakcia) 4 mg/m <sup>3</sup> (inhalovateľná frakcia)
Switzerland	VME (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Switzerland	Remark (CH)	(alveolengängige Fraktion)

### 8.2. Exposure controls

Appropriate engineering controls	: Avoid creating mist or spray. Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: None under normal use. In case of repeated or prolonged contact wear gloves. Use rubber gloves. EN374.
Eye protection	: None under normal use. In case of splashing or aerosol production: protective goggles. EN166.
Respiratory protection	: None under normal use. In case of inadequate ventilation wear respiratory protection. Use an approved respirator equipped with oil/mist cartridges. EN 12083.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Variable.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: 1.7
Melting point	: No data available
Freezing point	: -88.88 °C
Boiling point	: 82.5 °C
Flash point	: 12 °C
Auto-ignition temperature	: 399 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour
Vapour pressure	: 4 kPa (30 mm Hg) @ 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: 64.59 %
-------------	-----------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Highly flammable liquid and vapour.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Open flame. Direct sunlight. Heat.

### 10.5. Incompatible materials

Strong oxidizing agents.

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 10.6. Hazardous decomposition products

May release flammable gases. Thermal decomposition generates : Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity** : Not classified

<b>ethanol (64-17-5)</b>	
LD50 oral rat	10470 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (mg/l)	133.8 mg/l/4h
ATE CLP (oral)	10470.000 mg/kg bodyweight
ATE CLP (vapours)	133.800 mg/l/4h
ATE CLP (dust,mist)	133.800 mg/l/4h

<b>Isopropanol (67-63-0)</b>	
LD50 oral rat	5840 mg/kg
LD50 dermal rabbit	16.4 ml/kg
LC50 inhalation rat (ppm)	> 10000 ppm/4h
ATE CLP (oral)	5840.000 mg/kg bodyweight

<b>propyl acetate (109-60-4)</b>	
LD50 oral rat	8700 mg/kg
LD50 dermal rabbit	> 17800 mg/kg
LC50 inhalation rat (mg/l)	32 mg/l/4h
ATE CLP (oral)	8700.000 mg/kg bodyweight
ATE CLP (vapours)	32.000 mg/l/4h
ATE CLP (dust,mist)	32.000 mg/l/4h

<b>Butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 inhalation rat (mg/l)	> 21 mg/l/4h
ATE CLP (oral)	10760.000 mg/kg bodyweight

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LD50 oral rat	8532 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (ppm)	4345 ppm 6 h
ATE CLP (oral)	8532.000 mg/kg bodyweight

<b>2-methoxypropyl acetate (70657-70-4)</b>	
LC50 inhalation rat (ppm)	2700 ppm 6 h

<b>Titanium dioxide (13463-67-7)</b>	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 6.82 mg/l/4h

<b>Aluminum oxide (1344-28-1)</b>	
LD50 oral rat	> 15900 mg/kg
LC50 inhalation rat (mg/l)	7.6 mg/l/4h
ATE CLP (vapours)	7.600 mg/l/4h
ATE CLP (dust,mist)	7.600 mg/l/4h

<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7)</b>	
LD50 oral rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	> 1580 mg/m <sup>3</sup> 4 h

<b>C.I. Solvent Black 29 (117527-94-3)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight

**Skin corrosion/irritation** : Not classified

**Serious eye damage/irritation** : Not classified

**Respiratory or skin sensitisation** : Not classified.

**Germ cell mutagenicity** : Not classified

**Carcinogenicity** : Not classified.



# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

<b>Titanium dioxide (13463-67-7)</b>	
NOAEL (chronic, oral, animal/male, 2 years)	5 mg/kg bodyweight rat
<b>Reproductive toxicity</b>	: Not classified
<b>Specific target organ toxicity (single exposure)</b>	: Not classified
<b>Specific target organ toxicity (repeated exposure)</b>	: Not classified
<b>Aspiration hazard</b>	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>ethanol (64-17-5)</b>	
LC50 fish 1	14200 mg/l
EC50 Daphnia 1	5012 mg/l
<b>Isopropanol (67-63-0)</b>	
LC50 fish 1	10000 mg/l
<b>propyl acetate (109-60-4)</b>	
LC50 fish 1	60 mg/l 96 h
EC50 Daphnia 1	91.5 mg/l 48 h
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LC50 fish 1	100 - 180 mg/l
EC50 Daphnia 1	> 500 mg/l 48 h
ErC50 (algae)	> 1000 mg/l
<b>Aluminum oxide (1344-28-1)</b>	
EC50 Daphnia 1	> 1470 mg/l
NOEC (acute)	> 50 mg/l
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7)</b>	
LC50 fish 1	> 500 mg/l 96 h
EC50 Daphnia 1	> 110 mg/l 48 h
<b>C.I. Solvent Black 29 (117527-94-3)</b>	
LC50 fish 1	2 mg/l 96 h

### 12.2. Persistence and degradability

<b>ethanol (64-17-5)</b>	
Biodegradation	> 96 % 28 d
<b>Isopropanol (67-63-0)</b>	
Persistence and degradability	Readily biodegradable.
<b>propyl acetate (109-60-4)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	62 % 5 d
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	89 % 10 d
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d
<b>C.I. Solvent Black 29 (117527-94-3)</b>	
Persistence and degradability	Not readily biodegradable.

### 12.3. Bioaccumulative potential

<b>ethanol (64-17-5)</b>	
Bioaccumulative potential	Not expected to bioaccumulate.
<b>Isopropanol (67-63-0)</b>	
Bioaccumulative potential	Not expected to bioaccumulate.
<b>propyl acetate (109-60-4)</b>	
Log Pow	1.23

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Log Pow	0.43
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7)</b>	
BCF fish 1	53 l/kg
Log Pow	1.28
<b>C.I. Solvent Black 29 (117527-94-3)</b>	
Log Pow	< 3.7 @ 20 °C

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

<b>PRO-WASH™ D Detergent Removable Paint Markers</b>
PBT: not yet assessed
vPvB: not yet assessed

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used. 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR)	: 1263
UN-No.(IATA)	: 1263
UN-No. (IMDG)	: 1263
UN-No.(ADN)	: 1263

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Paint
Proper Shipping Name (IATA)	: Paint
Proper Shipping Name (IMDG)	: PAINT
Proper Shipping Name (ADN)	: PAINT
Transport document description (ADR)	: UN 1263 PAINT, 3, II, (D/E)

### 14.3. Transport hazard class(es)

Class (ADR)	: 3
Classification code (ADR)	: F1
Class (IATA)	: 3
Class (IMDG)	: 3
Class (ADN)	: 3
Classification code (ADN)	: F1

### 14.4. Packing group

Packing group (ADR)	: II
Packing group (IATA)	: II
Packing group (IMDG)	: II
Packing group (ADN)	: II

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### 14.6.1. Overland transport

Hazard identification number (Kemler No.) : 33


# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Classification code (ADR) : F1

Orange plates :



Tunnel restriction code (ADR) : D/E

EAC code : •3YE

### 14.6.2. Transport by sea

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-E

Stowage category (IMDG) : B

### 14.6.3. Inland waterway transport

Carriage prohibited (ADN) : No

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substance on the REACH candidate list

VOC content : 64.59 %

#### 15.1.2. National regulations

##### Germany

Water hazard class (WGK) : 2 - hazard to waters

WGK remark : Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

according to Regulation (EC) No. 453/2010

Indication of changes:

Revised format.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weight Average
	TSCA: Toxic Substances Control Act

Data sources : ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.  
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.  
Kristen Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.  
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.  
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

# PRO-WASH™ D Detergent Removable Paint Markers

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Other information : None.

Full text of R-, H- and EUH-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H360D	May damage the unborn child
H411	Toxic to aquatic life with long lasting effects
EUH208	Contains . May produce an allergic reaction
EUH210	Safety data sheet available on request
R10	Flammable
R11	Highly flammable
R36	Irritating to eyes
R36/38	Irritating to eyes and skin
R37	Irritating to respiratory system
R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R61	May cause harm to the unborn child
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant

LA-CO EU CLP SDS

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43016  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*